



MANUFACTURER OF FORMULATED CHEMICALS FOR INDUSTRY



SURFACE PROTECTION
TECHNOLOGIES

Technical Data Sheet

PRODUCT NAME: EZ GUARD™ HEAVY FILM 19

DESCRIPTION

EZ GUARD™ HEAVY FILM 19 is a rust preventative oil that can be applied by spray, brush or immersion. It gives excellent long term (30-60 days) rust protection under high humidity and acid vapour conditions. Its unique formulation allows it to be applied to hot metal.

ADVANTAGES

EZ GUARD™ HEAVY FILM 19 is a high quality preventative oil which imparts a uniform film. This allows for long term rust protection and good in-plant storage.

CONTROL PROCEDURE

EZ GUARD™ HEAVY FILM 19 is used as received. It should always be applied to a clean surface. Application methods include dipping, brushing or by a course spray. Dipping is the preferred method of application and should be applied as soon after cleaning as possible. **EZ GUARD™ HEAVY FILM 19** is a water displacing rust preventative, therefore may be applied directly after a water rinse. However, water should be dumped out of blind holes and cavities of production pieces before applying. Water will go to the bottom of the **EZ GUARD™ HEAVY FILM 19** tank and should be bled off periodically to prevent production pieces from being dipped in plain water and potential entrapment.